

**100% Air Powered
Folding Tail**



**Air Ride
Suspension**

“EASY TAIL” Low Profile 8-Tire Low Bed Trailer



Standard Features:

- ◇ Permitted NET Load - 32 Tons*
- ◇ 100% Air powered folding tail-No hydraulics required!
- ◇ Air Ride Suspension
- ◇ Guaranteed over-the-back loading!
- ◇ Murray mechanical detachable gooseneck
- ◇ Straight or tapered front corners of gooseneck
- ◇ GVWR: 80,000 lbs.
- ◇ GAWR: 2 axles@ 20,000 lbs. each
- ◇ Base trailer weight (approx.) - 14,200 lbs.*
- ◇ LED lighting

**Capacity and weight estimate are based on previously completed trailers; actual capacity may vary depending on pulling tractor and final options selected.*

REMEMBER, IT'S THE PAYLOAD THAT COUNTS!



Over-the-Rear Loading

Murray Trailers • 1745 E Mariposa Rd. • Stockton, CA 95205
Phone: 209-466-0266 • Online: www.murraytrailer.com



The Murray “Easy Tail”

Standard Features:

- Construction: 130 KSI/100 KSI yield steel
- Tail Loading Angle: 14.5 Degrees
- Axles: 2 each, 20,000 lbs. each
- Suspension: Air Ride Suspension
- Axle Spacing: 54-inches
- Wheels: Aluminum, 8-hole, hub piloted aluminum
- Tires: 235/75R x 17.5 - Hankook or Continental
- Decking: 3" Apitong outside, 2" Douglas Fir inside
- Paint: DuPont IMRON ELITE
- Goosenecks: Mechanical Removable wide neck for jeep or trailer
- Deck Height: 27" nominal center of deck (dependent on 5th wheel height)
- Over-front loading: 10"
- Over-rear loading: 34"
- Overall Length: 46'-10" with standard 21'-6" deck, gooseneck, & tail
- Width: 8' - 6"

*Capacity, Trailer Length, Deck length and King pin length subject to change depending on options selected.

Optional Features:

- Deck Lengths to 23'-4"
- 16" Longer Gooseneck
- Second kingpin
- Air operated "RoboLink" & Deck Latch release (US PAT #8752854, 9272591)
- Tire Inflation System
- Disc brakes with ABS
- Full or half wheel covers
- Electric Winch
- Lockable tool boxes in wide neck
- Front wedge & paver ramps
- "D" Rings
- Outriggers, removable or sliding
- Chain boxes
- Deck well or pan
- Cleral Scale System, wireless (AIR)
- Spare wheel & tire with lockable mount
- Rubber strips on tail



Electric Winch, Spare Tire
w/ Mount , & Lockable Tool
Boxes



Removable Wheel Covers



Sliding Outriggers &
Paver Ramps



Deck Pan &
Chain Box

Model ODDD: Open Tire, Double Drop, Detachable Gooseneck

