

*Low Profile
17.5 Wheels & Tires*



*Air Ride
Suspension*

“INTERSTATE” Low Profile 45 Ton 3 - Axle Trailer



Standard Features:

- ◇ Permitted NET load in all 50 states & Canada - 45 TONS*
- ◇ Guaranteed over-the-back loading
- ◇ Base trailer weight (approx.) 15,500 lbs. (21'6" Deck)
- ◇ Air-Ride Suspension w/ dump valve & scaling gauge
- ◇ Murray Mechanical Detachable Gooseneck with straight or tapered corners
- ◇ Hankook or Continental 235/75R17.5 Tires
- ◇ Straight or tapered front corners of gooseneck
- ◇ GVWR 100,000 lbs.
- ◇ LED lighting
- ◇ 8-Hole, Hub Piloted Aluminum Wheels - 4 Polished

*Capacity and weight estimate are based on previously completed trailers.
Actual capacity may vary depending on pulling tractor and options selected.

REMEMBER, IT'S THE PAYLOAD THAT COUNTS!



Over-the-Rear Loading

Murray Trailers • 1745 E Mariposa Rd. • Stockton, CA 95205
Phone: 209-466-0266 • Online: www.murraytrailer.com



The Murray “INTERSTATE”

Standard Features:

- Construction: 130 KSI/100 KSI yield steel
- Axles: 3 Axles at 20,000 lbs. each; 54” axle spacing
- Suspension: Air-Ride Suspension w/ dump valve, scaling guage, & rear axle lift
- Capacity: 45 Tons
- Wheels: 8-hole, hub piloted aluminum; outside wheels polished
- Tires: 235/75R x 17.5 - Hankook or Continental
- Decking: 3” Apitong outside, 2” Douglas Fir inside
- Paint: DuPont IMRON ELITE
- Goosenecks: Mechanical Removable wide neck with a single kingpin
- Deck Height: 27” nominal center of deck (dependent on 5th wheel height)
- Over-front loading: 10”
- Over-rear loading: 36”
- Overall Length: 45’-8” with standard 21’-6” deck, gooseneck, 54” axle spacing, and standard tail

Optional Features:

- Deck Lengths to 24’
- 60 Inch Axle Spacing
- 16” Longer Gooseneck
- Second kingpin
- Air operated “RoboLink” & Deck Latch release (US PAT #8752854, 9272591)
- Manual or Sliding Outriggers
- Disc brakes with ABS
- Full wheel covers
- Tire Inflation System
- Lockable tool boxes in wide neck
- Front & rear loading ramps
- ”D” Rings
- Cleral Scale System
- Chain boxes w/ optional lids
- Excavator deck well or pan
- Rear Diamond Ramp storage w/ air lock
- Spare tire with lockable mount
- Electric winch on gooseneck
- 20 ‘ Longer sloping tail for rear loading



Lockable Tool Boxes & Spare Tire w/ Mount



Wheel Covers & Extended Tail



Ramp Storage



Sliding Outriggers & Paver Ramps



Outside Lines for Robolinks



Deck Pan & Chain Box